

CP-UVR-0401E1-CV2

4Ch. 1080N Digital Video Recorder

- Supports HDCVI/AHD/TVI/CVBS/IP video inputs
- Max. 5 channels IP camera inputs, each channel up to 2MP;
Max 20Mbps Incoming Bandwidth
- Support 1 SATA HDD up to 6TB, 2 USB Ports
- 1 HDMI / 1 VGA Simultaneous Video Output
- Instastream, H.265, H.264+, H.264 video compression
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro Lite



System Overview

CP Plus has introduced the new and impactful range of DVRs under the Lite Series which has been integrated with the 4K and H.265 encoding technology that provides you with an outstanding at a reasonably pocket-friendly price. The 4K resolution processors present in this product help in bringing out every little detail in the image. Along with that, this DVR uses the intuitive shortcut operation menu which lets you control and manage the system remotely as well and can work as edge storage, central storage, backup storage .

The highly compatible design of this DVR allows you to third-party devices. This makes this product the ideal solution to your surveillance requirements as it can run independently of video management systems. This DVR by CP Plus has wide-ranging applications such as in keeping the public safe, conserving the water, transportation, city centers, educational facilities, and other institutions .



CP-UVR-0401E1-CV2

4Ch. 1080N Digital Video Recorder

Functions

Signal auto-adapt

This DVR recognizes the signal type (CVI, TVI, AHD, CVBI) and automatically adapts without requiring any manual intervention. This has provided much ease to the user since signal compatibility was always a towering concern.

Addnl. IP cameras support

In some installations, customers have specific features and functions that are available in IP cameras only, such as two-way communication, edge storage, alarm I/O, etc. CP PLUS DVRs provide additional IP camera support to provide flexibility so that the desired solution features can be made accessible.

Secured Password Policy (SPP)

Amid rising security challenges such as hacking, phishing, etc., CP PLUS has framed strict policies to increase the security of surveillance systems, in which it makes it mandatory to change the default password to one that is alphanumeric.

Multi-signal Support

CP PLUS DVRs are equipped with UNI+ technology which supports all HD and analog video formats. This helps the user upgrade their systems without requiring major overhauls.

gCMOB/ iCMOB

Designed to allow users to access and control live streaming from CP PLUS IP Cameras, DVRs/ NVRs and Video Door Phones, the CP PLUS gCMOB/ iCMOB application offers a host of features such as Easy GUI, up to 16 live viewing split-ups; InstaOn cloud support; Playback; digital zoom ins; two-way talk, and more.

KVMS Pro

The KVMS Pro is a hybrid security management software that allows the management of various surveillance devices such as cameras, DVRs/ NVRs, encoders/ decoders, etc. It is released with the surveillance hardware and exclusively supports CP PLUS devices.

About CP PLUS

The brand that is on its way to lead the world when it comes to the security and surveillance industry, CP PLUS, keeps bombarding the market with the most reliable range of products that have been designed carefully and methodically to automate the whole surveillance and security process, no matter how big your premises are.

It was the initiative to help the public in the area where they are the most vulnerable and to empower the sense of safety in our hearts that had conceptualized CP PLUS. And embarking on its mission to make the world a safer and more secure place has taken the brand's journey to unprecedented levels even when compared to international competitors.



CP-UVR-0401E1-CV2

4Ch. 1080N Digital Video Recorder

Feature	Specification
Processor	Embedded processor
Operating System	Embedded LINUX
IP Camera Input	4+1 channels, each channel up to 2MP
Two-way Talk	Reuse audio in/out, RCA
User Interface	GUI
Video Input	4 channel, BNC
Video Output	1 HDMI, 1 VGA
Resolution	Recording: 1080N, 720P, 960H, D1, HD1, BCIF, CIF, QCIF; Display: 1920×1080, 1280×1024, 1280×720, 1024×768
Video Display Split	1/4
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording
Bit Rate	32 kbps–4096 kbps per channel
Audio Input	1 channel, RCA
Audio Output	1 channel, RCA
Motion Detection	Supports
Video Loss	Supports
Camera Blank	Supports
Video Compression	Instastream, H.265, H.264+, H.264
Audio Compression	G.711A; G.711U; PCM
Audio Sample Rate	8 KHz, 16 bit per channel
Smart Phone	iPhone, iPad, Android Phone
Hard Disk	1 SATA port, up to 6TB Each
Audio Bit Rate	64 kbps per channel
Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tip

Feature	Specification
Recording Mode	Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second)
Playbackfunction	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup, selection, Digital zoom
Playback	1/4 Ch.
Backup Mode	USB Device
Record rate	Main Stream: All channel 1080N/720P/960H/D1/CIF(1~25/30fps); Sub stream: CIF/QCIF (1~15fps)
Interface Ports	2 USB Ports(2.0)
Max User Account	128 users
Record Interval	1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec
Ethernet	1 RJ-45 Port (100 MB)
Protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, Alarm Server, InstaOn, IP Search, ONVIF 16.12, CGI Conformant
Power Supply	DC12V/1.5A
Power Consumption	<10W (without HDD)
Operating Temperature	-10°C ~ +45°C (+14°F~+113°F)
Storage Temperature	-20°C ~ +70°C (-4°F~+158°F)
Operating Humidity	10 ~ 90% (RH)
Storage Humidity	0 ~ 90% (RH)
Dimensions	198 mm × 202.9 mm × 41.5 mm
Weight	0.55kg (without HDD)

Dimensions (mm/inch)

Company Name:

CP PLUS (Aditya Infotech Ltd.)

F-28 Okhla Industrial Area, Phase 1,

New Delhi 110020, INDIA

Contact Mail ID :- customercare@cpplusworld.com