



GHP620(W)



GHP621(W)

Not an LCD Display*

Compact Hotel Phone

GHP620 • GHP620W • GHP621 • GHP621W

The GHP Series of hotel phones feature the GHP620/GHP620W and GHP621/GHP621W, easy-to-use IP phones for any hotel room that can be programmed and customized based on the needs of hotels and their guests. The GHP620W and GHP621W models are equipped with integrated dual-band Wi-Fi to support wireless deployments. This Series features an HD speaker, 2 SIP accounts/lines, 6 programmable keys, 10 speed dial keys, 3-way voice conferencing, supports the full-band OPUS voice codec and provides an advanced jitter-resilience algorithm that tolerates up to 30% packet loss without impacting voice quality. The GHP Series is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints. GHP series IP phones can be installed on desktop or wall-mounted and can be powered by PoE (GHP620/GHP621), or power adapter (GHP620W/GHP621W). Thanks to a sleek and compact design, the GHP620/GHP620W and GHP621/GHP621W are the ideal fit for not only hotels but also apartments, dormitories, hospitals, retail and much more.



2 SIP accounts, 2 lines



GDMS online device management and provisioning



3-way audio conferencing for easy conference calls



Integrated dual-band 2.4GHz & 5GHz 802.11 a/b/g/n/ac (GHP620W & GHP621W only)



Includes one 100Mbps network port with PoE (GHP620 & GHP621 only)



Swappable faceplate to allow for easy logo customization



Hearing Aid Compatibility (HAC)



Enterprise-level protection including secure boot

Protocols/Standards	SIP: SIP RFC3261, TCP/IP/UDP, RTP/RTCP, RTCP-XR, TLS, SRTP Network: IPv4, IPv6, HTTP/HTTPS, ARP, ICMP, DNS(A record, SRV, NAPTR), DHCP, SSH, TFTP, NTP, STUN, LLDP, TR-069, 802.1x
Network Interfaces	One auto-negotiation 10/100 Mbps ethernet port integrated PoE Class 2 (GHP620/GHP621)
Wi-Fi	GHP620W/GHP621W integrated dual-band 2.4GHz & 5GHz 802.11 a/b/g/n/ac
Feature Keys	26 keys, including: 6 programmable keys; 12 Standard Phone Digits keys (0-9: speed dial keys configuration on web page, * , #); 5 Function keys (Flash, Redial, Hands-free, Voice Mail, Hold); 3 Volume Control keys, Up/Down/Mute (with red color LED)
HD Audio	One HD handset support for wide band audio
Voice Conferencing	2 SIP accounts and lines, up to 3-way conference
Voice Codecs and Capabilities	Support for G.729A/B, G.711μ/a-law, G.726, G.722 (wide-band), G.723, iLBC, full band Opus, In-band and out-of-band DTMF (in audio, RFC2833, SIP INFO), VAD, AEC, CNG, PLC, AGC, AJB
Telephony Features	Dial, Answer, Redial, Flash ,Hands-free, Voice Mail(with the server), Transfer, Conference, Hold /Unhold, Mute /Unmute, flexible dial plan, Speed dial server redundancy & fail-over Call out
Advanced Features	Support for multicast paging and E911 service. Support GDS Door opening. Support for advanced jitter-resilience algorithm.
USB	USB Type-C port for charging external devices (500mA MAX)
Wall Installation	1 Wall Mountable Base
QoS	Layer 2 QoS (802.1Q, 802.1p) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	Secure boot, random default password, unique security certificate per device, administrator level passwords, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control
Multi-language	English and Chinese
Upgrade/Provisioning	Firmware upgrade via FTP / TFTP / HTTP / HTTPS, fast boot in 15 seconds, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file
Power & Green Energy Efficiency	Universal power adapter (GHP620W/GHP621W): Input: 100~240Vac 50~60Hz Output: 12V/0.5A(6W)
Temperature and Humidity	Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% (Non-condensing)
Package Content	GHP phone, handset with cord, Base Stand, universal power supply (GHP620W, GHP621W), faceplate, Quick Installation Guide
Color	White (GHP620,GHP620W), Black (GHP621,GHP621W)
Physical	210mm(L)*132mm(W)*89.8mm(H) (with handset and base stand) Unit weight: 560g (GHP620/GHP621), 610g (GHP620W/GHP621W US), 620g (GHP620W/GHP621W World) Package weight: 860g (GHP620/GHP621), 910g (GHP620W/GHP621W US), 920g (GHP620W/GHP621W World)
GHP620 & GHP621 Compliance	FCC: Part 15 Subpart B, Class B; Part 68. 316/317. CE: EN 55032; EN 55035; EN IEC 61000-3-2; EN 61000-3-3; EN IEC 62368-1. UKCA: BS EN 55032; BS EN 55035; BS EN IEC 61000-3-2; BS EN 61000-3-3; BS EN 62368-1. RCM: AS/NZS CISPR32; AS/NZS 62368.1; AS/CA S004. IC: ICES-003; CS-03 Part V.
GHP620W & GHP621W Compliance	FCC: Part 15 Subpart B, Class B; Part 15 Subpart C,15.247; Part 15 Subpart E,15.407; Part 68. 316/317. CE: EN 55032; EN 55035; EN IEC 61000-3-2; EN 61000-3-3; EN IEC 62368-1; ETSI EN 301489-1\1-17; ETSI EN 300 328; ETSI EN 301 893; EN IEC 62311. UKCA: BS EN 55032; BS EN 55035; BS EN IEC 61000-3-2; BS EN 61000-3-3; BS EN 62368-1; ETSI EN 301489-1\1-17; ETSI EN 300 328; ETSI EN 301 893; BS EN IEC 62311. RCM: AS/NZS CISPR32; AS/NZS 4268; AS/NZS 2772.2; AS/NZS 62368.1; AS/CA S004. IC: RSS-247; RSS-Gen; RSS-102; ICES-003; CS-03 Part V.