

D-Link[®]**Indigenous**
SERIES**DCS-F5712-L1**

2 Mega Pixel Bullet IP Camera with Audio

High-definition professional surveillance and security solution, suitable for small and medium enterprises.



Key Features



1/2.9" 2MP Progressive CMOS Sensor



3.6mm Fixed Lens



IP66 Compliant



H.264 & H.265, Dual-Stream Encoding



30 Meters IR Distance



PoE Enabled

Specifications

| Parameters | Specification |
|----------------------|--|
| Image Sensor | 1/2.9" 2MP Progressive CMOS Sensor |
| Effective Pixels | 1920(H)x1080(V) |
| Minimum Illumination | Color: 0.01 Lux @F1.2, B/W: 0.001 Lux@F1.2 |
| S/N Ratio | >60dB |
| IR Distance | IR Distance 30Mtr |
| Shutter Speed | Auto, Manual Mode: 1/50 sec 1/10000 sec |
| DWDR | Yes |
| IR On/Off Control | Auto/ Manual |
| IR LEDs | 18 Smart LED |
| Lens | |
| Lens Type | Fixed |
| Mount Type | M12 |
| Focal Length | 3.6mm Lens |
| Max. Aperture | F1.2 |
| Angle of View | Horizontal Angle- 74°, Vertical Angle- 58°, Diagonal Angle- 88° |
| Focus Control | Fixed |
| Video | |
| Compression | H.264 / H.265 |
| Streaming Capability | 2 Streams |
| Resolution | 1080P (1920×1080/ 720P(1280×720)/D1(704×576/704×480)/ VGA (640×480)/ CIF (352×288) |
| Streams | Mainstream: 1080P (1920*1080) @25FPS, Sub Stream: D1/ VGA/ CIF @25 FPS |



Specifications

| Parameters | Specification | Parameters | Specification |
|------------------|---|-----------------------|---|
| Frame Rate | 2MP @25/30fps | Safety | |
| Bit Rate Control | CBR/VBR | ONVIF Authentication | ON, OFF |
| Bit Rate Range | 27Kbps~8Mbps | RTSP Authentication | Digest, None |
| Day/Night | Automatic/Black and white | Audio | |
| Exposure Mode | Automatic/Manual-(1-1/10000) | Compression | G.711A/U |
| BLC Mode | On/Off | Network | |
| HLC Mode | On/Off | Ethernet | 1 x RJ45, 10/100M adaptive |
| AGC | Yes | | Ethernet interface |
| Profiles | Auto, Low Light Priority, High Light Priority | Protocol | IPv4,TCP/IP, HTTP, HTTPS, UDP, RTSP, FTP, DHCP, DDNS, NTP, SMTP, UPnP, Alarm Server, IP filter |
| Noise Filter | Auto,2D/ 1-5 Levels | Interoperability | ONVIF Profile S |
| Digital Zoom | 16X, Area selection with Mouse | Max. User Access | 30 Users |
| Anti-Flicker | On/Off | Edge Storage | Local PC for instant recording, One click Snapshot, One clicks triple Snapshot |
| I frame Interval | 1 to 20 | Web Viewer | IE, Chrome, Firefox, Safari |
| Noise Reduction | Yes | Management Software | D-Link Vision VMS |
| White Balance | Yes | Smart Phone | Supports D-Link Vision APP for iPhone, Android |
| AE reference | 1-255 Level | Interface | |
| AE Sensitivity | 1-10 Level | Audio | 1 In |
| Flip | Off / On | General | |
| IR reverse | Support | Operating Conditions | -30° C ~ +60° C / Less than 95% RH |
| Mirror | Off / On | Storage Conditions | -30° C ~ +60° C / Less than 95% RH |
| Text Overlay | Title, Date & Time, Weekday | Ingress protection | IP66 Complaint |
| Privacy Masking | 4 Private masking options | Vandalism protection | NA |
| Events | | Power Rating | DC 12V / 1Amp |
| Motion Detection | Yes | Power Consumption | Max 12W |
| Video Blind | Support | Dimension & Weight | 166mm(L) x 67mm(W) x 66(H), 160 g |
| Abnormality | No Disk, Disk Error, Disk No Space, Network Cable Disconnected, IP Address Conflict | Product Certification | Safety: CE, BIS |
| Smart Functions | Human Detection, Vehicle Detection, Line Crossing & Area Intrusion | | |
| Event Actions | Record alarm, Linkage alarm output, Sound alarm, Email link, Upload FTP, Snapshot | | |
| PTZ | | | |
| Pan/Tilt Range | Pan:0° ~360°; Tilt:0° ~90°; | | |

D-Link Indigenous series range of IP Surveillance solution includes:

DCS-F5612-L1: 2MP Mega Pixel Dome IP Camera with Audio

DCS-F5712-L1: 2MP Mega Pixel Bullet IP Camera with Audio

DCS-F5614-L1: 5MP Mega Pixel Dome IP Camera with Audio

DCS-F5714-L1: 5MP Mega Pixel Bullet IP Camera with Audio

DNR-F5104-M5: 4 Channel 1 SATA NVR

DNR-F5108-M5: 8 Channel 1 SATA NVR

DNR-F5216-M5: 16 Channel 2 SATA NVR

DNR-F5232-M5: 32 Channel 2 SATA NVR