

D-Link[®]**Indigenous**
SERIES**DCS-F5715-L1C**

5 Mega Pixel Bullet Color Camera with Audio



High-definition professional surveillance and security solution, suitable for small and medium enterprises.

Key Features



1/3" 5MP Progressive CMOS Sensor



3.6mm Fixed Lens



PoE Enabled



H.264 & H.265, Dual-Stream



Up to 30 Meters White Light Distance



IP66 Compliant

Specifications

Parameters	Specification
Image Sensor	1/3" 5MP Progressive CMOS Sensor
Effective Pixels	2592(H)x1944(V)
Minimum Illumination	Color: 0.001 Lux @F1.2,
S/N Ratio	>60dB
White light distance	Up to 30Mtr
Shutter Speed	Auto, Manual Mode: 1/50 sec 1/10000 sec
DWDR	Yes
IR On/Off Control	Auto/ Manual
LEDs	4pcs White LED
Lens	
Lens Type	Fixed
Mount Type	M12
Focal Length	3.6mm Lens
Max. Aperture	F1.2
Angle of View	Horizontal Angle- 72°, Vertical Angle- 54°, Diagonal Angle- 86°
Focus Control	Fixed
Video	
Compression	H.264 / H.265
Streaming Capability	2 Streams
Resolution	5MP (2592X1944)/4MP (2560X1440)/1080P(1920x1080)/ 720P(1280x720)/ D1(704x576) / VGA (640x480)/ CIF (352x288)
Streams	Mainstream: 5MP (2592X1944) @20FPS/ 4MP (2560X1440)/2MP (1920x1080) @25/30FPS, Sub Stream: D1 (704x576)/VGA (640x480)/ CIF (352x288) @25/30FPS



Specifications

Parameters	Specification	Parameters	Specification
Frame Rate	5MP @25/30fps	Safety	
Bit Rate Control	CBR/VBR	ONVIF Authentication	ON, OFF
Bit Rate Range	221Kbps~8Mbps	RTSP Authentication	Digest, None
Day/Night	Automatic/Black and white	Audio	
Exposure Mode	Automatic/Manual-(1-1/10000)	Compression	G.711A/U
BLC Mode	On/Off	Network	
Profiles	Auto, Low Light Priority, High Light Priority	Ethernet	1 x RJ45, 10/100M adaptive Ethernet interface
Noise Filter	Auto,2D/1-5 Levels	Protocol	TCP/IP, IPv4, ICMP, HTTP, HTTPS, HTTP-Base64, HTTP-Digest, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, FTP, IGMP, P2P, IP Filter
Digital Zoom	16X, Area selection with Mouse	Interoperability	ONVIF Profile S
Anti-Flicker	On/Off	Max. User Access	30 Users
I frame Interval	1 to 20	Edge Storage	Local PC for instant recording, One click Snapshot, One clicks triple Snapshot
Noise Reduction	Yes	Web Viewer	IE, Chrome, Firefox, Safari
White Balance	Yes	Management Software	VMS
AE Reference	1-255 Level	Smart Phone	Supports VMS APP for iPhone, Android
AE Sensitivity	1-10 Level	Interface	
Flip	Off / On	Audio	1 In
Mirror	Off / On	General	
Text Overlay	Title, Date & Time, Weekday	Operating Conditions	-30° C ~ +60° C / Less than 90% RH
Privacy Masking	4 Private masking options	Storage Conditions	-30° C ~ +60° C / Less than 90% RH
Events		Ingress protection	IP66
Motion Detection	Yes	Vandalism protection	NA
Video Blind	Support	Power Rating	DC 12V / 1Amp, PoE
Abnormality	No Disk, Disk Error, Disk No Space, Network Cable Disconnected, IP Address Conflict	Power Consumption	Max 12W
Smart Functions	Human Detection, Line Crossing & Area Intrusion	Dimension & Weight	164.5 x 67.4 x 67.4mm 300 g
Event Actions	Record alarm, Linkage alarm output, Email link, Upload FTP, Snapshot	Product Certification	Safety: CE, BIS
PTZ			
Pan/Tilt Range	Pan:0° ~360°; Tilt:0° ~90°; Rotation:0° ~360°		