

## DNR-F5216-M8

### 16CH Network Video Recorder



## KEY FEATURES

- 16CH, 2 SATA NVR
- Support up to 8MP IPC
- Support H.265+/H.265/H.264+/H.264
- Support Smart Playback & Analytics
- Support 3G/4G Wi-Fi Connectivity
- Support Google Drive & Dropbox Cloud storage
- Support Onvif 2.6
- Support 1CH Audio

## SPECIFICATION

## Video &amp; Audio Input

IP Video Input	16ch
----------------	------

Two Way Talk	1-ch, RCA
--------------	-----------

## Video &amp; Audio Output

HDMI	1ch, resolution:4K(3840×2160)/30Hz,1920×1080/60Hz,1440×900/60Hz,1280×1024/60Hz, 1280×720/60Hz, 1024×768/60Hz
------	---

VGA	1ch, resolution:1920×1080/60Hz,1440×900/60Hz,1280×1024/60Hz, 1280×720/60Hz,1024×768/60Hz
-----	---

Audio Output	1-ch, RCA
--------------	-----------

## Recording

Compression	H.265+/H.265 /H.264+/H.264
-------------	----------------------------

Resolution	8MP/5MP/4MP/3MP/1080P/720P/D1/CIF /QCIF
------------	---

Bit Rate	64Kbps~10Mbps
----------	---------------

## Playback &amp; Backup

Playback Mode	Smart/ Normal/ Time Division/ Label/ Event/ Picture/ Log Playback
---------------	---

Decoding Capability	4CH@1080P(25fps)
---------------------	------------------

Backup Mode	USB Device/Network
-------------	--------------------

## Advanced Features

Smart Detection	Line crossing, Area Intrusion, Fast moving, Unattached Object, Object Missing
-----------------	---

Smart Playback	Line Crossing/Area Intrusion /Motion Detection
----------------	--

Cloud Storage	Support
---------------	---------

Cloud Upgrade	Support
---------------	---------

## Network

Incoming Bandwidth	160Mbps
--------------------	---------

Outgoing Bandwidth	256Mbps
--------------------	---------

Ethernet	1 RJ-45 10 /100/1000 Mbps self-adaptive Ethernet interface
----------	--

Network Compatibility	HTTP, HTTPS, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, DDNS, FTP, P2P, ONVIF 2.6
-----------------------	---

Smart Phone	IOS (iPhone, iPad), Android (Phone, Pad)
-------------	--

Hard Disk	
SATA	2 SATA interface
Capacity	Up to 8TB capacity for each HDD
External Interface	
USB Interface	Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0
Alarm In	8CH
Alarm Out	1CH
General	
Power Supply	DC12V 3.3A
Power Consumption	≤10W (without HDD)
Working Environment	-10°C~+55°C / 10%~90%RH
Dimension (W×D×H)	326*243*52mm
Weight	≤2.3Kg
Certification	CE, BIS
System Management	
Mobile Software	D-Link Smart CCTV App
Desktop Software	DSVS (D-Link Smart Video Surveillance)
System Requirement for Web Interface	IE