

DVR-F2104-L1H5

4CH H.265+ 2MP Lite DVR



KEY FEATURES

- Supports 4CH & 1 SATA slot
- Supports AHD/TVI/CVI/IP cameras up to 2MP
- Supports H.264/H.264+/H.265/H.265+
- Supports Tamper & Video Loss Detection
- Supports 2 extra IP Channel
- Supports 3G/4G Wi-Fi
- Supports Cloud storage

DVR-F2104-L1H5

4CH, H.265+ 2MP Lite DVR

INTERFACE



SPECIFICATION

| VIDEO & AUDIO INPUT | | |
|----------------------|---|--|
| Video Input | 4ch BNC interface (1.0Vp-p, 75 Ω) | |
| TVI / CVI /AHD | 1080P, 720P | |
| IPC | Up to 6ch Resolution up to 2MP | |
| Audio Input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) | |
| Two way Talk | 1-ch, multiplex with Audio Input (RCA) | |
| VIDEO & AUDIO OUTPUT | | |
| HDMI | 1ch, resolution: 1920×1080/60Hz,1280×1024/60Hz, 1280×720/60 Hz, 1024×768/60Hz | |
| VGA | 1ch resolution: 1920×1080/60Hz, 1280×1024/60Hz,1280×720/60Hz,1024×768/60Hz | |
| CVBS output | NA | |
| Audio Output | 1-ch, RCA (Linear, 1kΩ) | |
| RECORDING | | |
| Compression | H.264/H.264+/H.265/H.265+ | |
| Resolution | 4ch 1080P Lite@15fps; 960H1/D1/CIF real time | |
| Frame Rate(fps) | 1fps-15fps | |
| Video Bit Rate | 11Kbps-2707Kbps | |
| Record Mode | Manual, Schedule, Alarm | |
| Audio Compression | G.711a | |
| Audio Bit Rate | 64Kbps | |
| PLAYBACK & BACKUP | | |
| Playback Mode | Normal/Time Division/ Label/ Event/ Picture Playback | |
| Playback Rate | 4ch Playback | |
| Backup Mode | USB Device/Network | |
| CLOUD FUNCTION | | |
| Cloud Storage | Support | |
| Cloud Upgrade | Support | |
| NETWORK | | |
| Ethernet | 1 RJ-45 10/100 Mbps self-adaptive Ethernet interface | |
| Network Function | HTTPs,HTTP,TCP/IP,IPv4,UPnP,Onvif2.6,RTSP, RTCP,UDP,SMTP,IGMP,NTP,DHCP,DNS,DDNS, FTP, P2P | |
| Smart Phone | IOS (iPhone, iPad), Android (Phone, Pad) | |

DVR-F2104-L1H5

4 CH, 2MP Lite DVR

| HARD DISK | |
|--------------------------------------|-------------------------------------|
| SATA | 1 HDD |
| Capacity | Up to 6TB capacity for each HDD |
| EXTERNAL INTERFACE | |
| Serial Interface | NA |
| USB Interface | 2 × USB 2.0 |
| GENERAL | |
| Power Supply | DC12V, 1.5A |
| Power Consumption | ≤15W(without HDD) |
| Working Environment | -10°C~+55°C / 10%~90%RH |
| Dimension (W×D×H) | 250 x 230 x 45mm |
| Weight (without HDD) | 1.5kg |
| Certification | CE, BIS |
| SYSTEM MANAGEMENT | |
| Mobile Software | D-Link Smart Plus CCTV App |
| Desktop Software | D-Link Smart Video Surveillance 2.0 |
| System Requirement for Web Interface | IE |

