



Revolutionary Products For The ISPs / WISPs



NM-012

**10/100Mbps Passive PoE Injector
12VDC @ 2A**



10/100Mbps Passive PoE Injector 12VDC @ 2A



NETSTAR Passive PoE Injector is used to power variety of Passive Wireless CPE & other PoE enabled devices (12VDC, 2A). NETSTAR PoE Injectors provide variety of features like Surge Protection, Overload & Short Circuit Protection.

TECHNICAL SPECIFICATION

Ethernet Connector	2 x 10/100Mbps Metallic RJ45 Ports
Input Voltage	100-240VAC @ 50/60Hz
Output Voltage	12VDC @ 2A (24Watt)
Network Cable	4-pair UTP Cat 5 / Cat 6 cable
LED	Power : On/Off for PoE Injector
Power Cord	By default : Indian Type 3 Pin Power Cord *Also available with all type of Power cords
Ethernet Cable Data Line	Pin 1,2 & Pin 3,6
Ethernet Cable Power Line	+VDC : Pin 4, 5 & -VDC : Pin 7, 8
Operating Temperature	0°C ~ 60°C
Storage Environment	-20°C ~ 80°C
Operating Humidity	20% to 95% (non-condensing)
Dimensions	50 x 110 x 35 mm
Net Weight	0.23 Kg

APPLICATION DIAGRAM

