

CP- UNR-4K4082-V2**8 Ch. 4K Network Video Recorder****Main Features**

- Up to 8 channel IP camera input
- Instastream/H.265/Smart H.264+/H.264
- Up to 8MP resolution preview and playback
- Max 200Mbps Incoming Bandwidth
- Support 2 SATA HDDs up to 10TB Each, 2 USB(1 USB3.0)
- HDMI / VGA simultaneous video output
- Support Multi-brand network cameras
- ONVIF Version 2.4 conformance
- Mobile Software: iCMOB, gCMOB
- CMS Software: KVMS Pro



CP- UNR-4K4082-V2

8 Ch. 4K Network Video Recorder

Feature

Processor
IP Camera Input
Operating System
Two-way Talk
User Interface
Video Output
Compression
Video Resolution
Network Bandwidth
Decoding Capacity
Recording Resolution
Video Display Split
Perimeter Protection by Camera Performance
AI Search
SMD Plus by Camera Performance
AI Search
Motion Detection
Video Loss
Camera Blank
Alarm Input
Alarm Output
Audio Input
Audio Output
Hard Disk
Smart Phone
Trigger Events

Specification

Dual-core embedded processor
8 channel
Embedded LINUX
1 channel Input, 1 channel Output, RCA
GUI
1 HDMI, 1 VGA
Instastream/H.265/Smart H.264+/H.264
HDMI: 3840×2160, 1920×1080, 1280×1024, 1280×720
VGA: 1920×1080, 1280×1024, 1280×720
200 Mbps for access, 200 Mbps for storage and 96 Mbps for forwarding
8 channels@1080P(30fps)
8MP/ 6MP/ 5MP/ 4MP/ 3MP/ 1080P/ 1.3MP/ 720P etc
1/4/8/9
8 channels
Search for pictures by channel, time and event type
8 channels
Search by target classification (human, vehicle)
MD Zones: 396(22×18).
Supports
Supports
4 Channel
2 Channel
1 channel, RCA connector
1 channel, RCA connector
2 SATA III ports, up to 10TB Each
iPhone, iPad, Android Phone
Recording, PTZ, Tour, Video Push, Email, Snapshot, Buzzer & Screen tips

CP- UNR-4K4082-V2

8 Ch. 4K Network Video Recorder

Feature

Recording Mode

Search Mode

Disk Group

General Alarm

Anomaly Alarm

Intelligent Alarm

Alarm Linkage

Playback Function

Backup Mode

Interface Ports

Max Remote Access

Record Interval

Ethernet

Protocols

Power Supply

Power Consumption

Working Temp

Dimensions

Weight

Specification

Manual, Schedule (Regular, Continuous), MD (Video detection: Motion Detection, Tampering, Video Loss), Stop

Time/Date, Alarm, MD & Exact search (accurate to second), Smart search

Support

Motion detection; privacy masking; video loss; PIR alarm; IPC alarm

Camera offline; storage error; full storage; IP conflict; MAC conflict; login lock; network security anomaly

Perimeter protection; SMD; people counting; heat map

Record; snapshot; IPC external alarm output; buzzer; log; preset; email

Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom

USB Device/Network

2 USB Ports (1 USB2.0, 1 USB3.0)

128 users

1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec

1 RJ-45 port (10/100M/1000Mbps)

HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, IGMP, ARP, SSL, ANR, RTP, QoS, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, SNMP, FTP, IP Search, ONVIF 2.4, SDK, CGI Conformance

DC12V/4A

<6.9W (Without HDD)

-10 ~+55°C / 10~90%RH / 86~106kpa

375mm x 281.5mm x 56mm

1.6kg (without HDD)