

SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



SATATYA MITC80FL36CWS P2
8MP All Color Camera with 3.6mm Lens

Matrix All Color Cameras are engineered to provide vibrant colored images even in challenging low-light or no-light scenarios. These cameras feature warm LEDs, ensuring full-color performance 24/7. With the turret enclosure, these cameras offer easy axis adjustment post-installation, minimize reflections with chambered LEDs, and reduce fingerprint smudges on the glass due to a smaller glass area.

Furthermore, the camera offers built-in video analytics such as motion detection, intrusion detection, tamper detection, and tripwire detection to aid you in proactively handling potential risks. Finally, backed by national and international certifications, these devices guarantee maximum operating time without failure.

USP



SONY STARVIS
SENSOR



H.265
COMPRESSION



IVA



HIGHER FIELD
OF VIEW



SMART
STREAMING



ADAPTIVE
STREAMING



TRUE WDR



NAS

CERTIFICATION



SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



TECHNICAL SPECIFICATIONS

IMAGE SENSOR

Resolution	8 MP (3840*2160)
Sensor Type and Size	1/2.8" SONY - CMOS 8MP Active Pixel Progressive Scan, Back Illuminated Image sensor (STARVIS Series)

LENS

Minimum Illumination	Color - 0.05 Lux @ F1.6(AGC ON) 0 Lux with Warm Light
Focal Length	3.6mm
Focus Range	0.3m to infinity
Field of View (FOV)	HFOV – 84° VFOV – 47.8° DFOV – 96.4°
Focus	Fixed focus
Aperture (F#)	F 1.6
Iris Type	Fixed
Type of Supplement LED	Warm LED
Supplement LED Range	Up to 30m
LED Switching	Auto/ Manual
DORI AS PER IEC 62676 - IV	D: 102m, O: 40 m, R: 21 m, I: 10 m

HARDWARE SPECIFICATIONS

Camera Adjustment Angle	Pan: 0° to 360° Tilt: 0° to 75° Rotate: 0° to 360°
-------------------------	--

IMAGE AND VIDEO

No of Stream Profiles	4
Stream Profiles	4k @30 FPS H.264, H.265 D1 @30 FPS H.264, H.265 3MP @10 FPS H.264, H.265, MJPEG 2MP @15 FPS H.264, H.265, MJPEG
Available Resolutions	3840 × 2160, 3200 x 1800, 2592 x 1944, 2592 x 1520, 2048 x 1536, 1920 x 1080, 720p, D1, 2CIF, VGA, CIF
Max Resolution	3840 × 2160
Bitrate	128 kbps-16Mbps
Bitrate Type	CBR, VBR
Video Compression	H.265, H.264, MJPEG
Frame Rate	1-30fps
Shutter Speed	1/15s -1/100000s
Adaptive Streaming	Yes
ONVIF Profiles	S,G & T

SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



Edge Recording	Yes (Only in NAS)
Alarm Recording	Pre and Post
Motion Recording	Yes
Video Parameters	Snapshot, Region of Interest (ROI), BLC, HLC/ Day/Night Settings
Privacy Masks	8
WDR	True WDR (120dB)
SNR	>70dB
Image Enhancement	Saturation/ Contrast/ Sharpness/Brightness/Auto Exposure/ HVS Forensic
DNR	2D &3D
Video Analytics	Motion Detection, No Motion Detection, Tamper Detection, Trip/No Trip Detection, Object Intrusion/Zone Intrusion
ALERTS	
IP Conflict	Yes
Network Disconnect	Yes
Storage Full	Yes
Time Triggered	Yes
EVENTS AND ACTIONS	
Upload Image	NAS, SFTP
Upload Clip	NAS, SFTP
Notifications	E-mail, SMS, TCP
PROTOCOLS SUPPORTED	
Supported protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, DNS, DynDNS, DDNS, RTP, RTCP, RTSP, PPPOE, SMTP, NTP, SNMP, FTP, TLS/SSL, SFTP, ICMP, IGMPv2 & v3, ARP, 802.1x, IPv4, IPv6, QoS Layer 3, DSCP, CIFS, SSH, UPnP, Bonjour
Web Viewer	Supported in IE 8.0-11.0, Firefox 15.0-47.0, Chrome 20.0-54.0
Browser	IE, Chrome, Mozilla
CYBER SECURITY as per ISO/IEC 27402	
Secure boot	Yes
Signed firmware	Yes
Data Encryption	All data, including sensitive data, is encrypted with AES 256 and RSA 2048
IP Address Filtering	Yes
HTTPs Streaming	Yes, using TLS 1.2
Edge Data Encryption	Yes
Network Authentication	Yes, 802.1x Network authentication
Secure Firmware Upgrade	Yes
Anti-roll back firmware	Yes
Web login Password	Yes
Unused Debug Interface Protection	Yes

SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



Operating Parameters	
Power Supply	802.3af (PoE)
Power Consumption	9W
Operating Humidity	Less than 95% RH (non-condensing)
Operating Temperature	-30°C to 60°C
PHYSICAL PARAMETERS	
Communication interface	10Base-T/100BaseTX Ethernet (RJ-45)
Weight	720g
Color	Infinity White
Dimensions	138.58mm x 118.97mm (Diameter x Height)
Certifications	BIS, CE, IP67, FCC Part-15 Subpart - B, ONVIF S,G,&T, NDAA Compliant, Essential Requirement (ER) by STQC


Specifications are subject to change without prior notification

SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



DIMENSIONS (in mm)



SATATYA MITC80FL36CWS P2

8MP All Color Camera with 3.6mm Lens



ABOUT MATRIX

Established in 1991, Matrix is a leader in security and telecom solutions for modern businesses and enterprises. Matrix, an innovative, technology driven and customer focused organization, is committed to keep pace with the revolutions in security and telecom industries. With more than 40% of its human resources dedicated to the development of new products, Matrix has launched cutting-edge products such as Unified Communications, IP-PBX, Universal Gateways, Convergence, VOIP Gateways, GSM Gateways, IP Video Surveillance, Access Control and Time-Attendance. These solutions are feature-rich, reliable and conform to the international standards. Having global footprints in Europe, North America, South America, Africa and Asia through an extensive network of more than 4000 channel partners, Matrix ensures that the products serve the needs of its customers faster and longer. Matrix has gained trust and admiration of customers representing the entire spectrum of industries. Matrix has won many national and international awards for its innovative products.



MATRIX COMSEC

Head Office

394 – GIDC,

Makarpura, Vadodara

– 390 010, India.

Ph: +91 265 613 7222

Email: Inquiry@MatrixComSec.com

Factory

19 – GIDC, Waghodia,

Dist. Vadodara – 391 760, India.

Ph: +91 265 613 7222

MATRIX COMSEC – North America

2 Wickstead

Crt,

Brampton,

Ontario – L6R 1N8.

Ph: (+1) 408-643-0581 (USA)

Ph: (+1) 437-266-1005 (Canada)

www.MatrixComSec.com