D-Link®
Building Networks for People

CAT6 STP PATCH CORDS

Cat6 STP Patch Cords

D-Link Cat6 patch cords are high quality four pair shielded twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA-568 C.2 standard. The shielded cables helps to complete a proper ground connection and allows longer runs with less effect of Electromagnetic Interference (EMI) and Radio Frequency Interference (RFI). These patch cords are appropriate for high speed data transmission.



SPECIFICATIONS

Conductor:	**26 AWG, Multi-cores**
Conductor Metal:	**Bare Copper**
Insulation Material:	**HD-PE**
Outside Tape Metal:	**Aluminum Foil**
Drain Wire:	**26 AWG**
Material:	**FR-PVC**
Color Code:	**Grey**
Heat Resistant:	**75°C Max**

Modular Connector/Plug :

RJ-45 8P for transparent color

Gold plated	: 03MU"
Contact Blade	: Copper Alloy
Dielectric withstanding voltage	: 1000V AC/ 1min no breakdow
Insulation resistance	: 500M min, 100V DC/min
UL applications	: PC UL94-V0

Application

100BASE-TX Fast Ethernet, 1000BASE-T,
Power over Ethernet (PoE)

ORDERING INFORMATION

Part Code	Description
NCB-C6SGRYR1-1	Cat6 STP 26AWG Patch Cord, 1M
NCB-C6SGRYR1-2	Cat6 STP 26AWG Patch Cord, 2M
NCB-C6SGRYR1-3	Cat6 STP 26AWG Patch Cord, 3M

Other lengths available on request

UL LISTED

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2020 D-Link Corporation. All rights reserved. Release 01 (May 2020)