D-Link®
Building Networks for People

Cat 6 UTP LSZH PATCH CORDS

Cat6 UTP Patch Cords

D-Link Cat6 patch cords are high quality four pair twisted stranded cable terminated with RJ45 modular plugs at both the ends. It is TIA/EIA-568-C.2 standard. These patch cords are appropriate for high speed data transmission.



SPECIFICATIONS

Conductor:	**24 AWG, Multi-strands**
Conductor Metal:	**Bare Copper**
Insulation Material:	**HDPE**
Outer Jacket:	**LSZH**
Material:	**PVC UL94V-0**
Color Code:	**Cool Grey 5C**
Heat Resistance:	**60˚C minimum (Temperature limited)**
Insertion Cycles:	**750 times**

Application

10BASE-T, 100BASE-TX Fast Ethernet, 1000BASE-T, 10GBASE-T (IEEE802.3)

100VG-AnyLAN (IEEE802.12)

550MHz Broadband Video

Voice, T1, ISDN

155/622 Mbps ATM

Power over Ethernet (PoE)

MODULAR CONNECTOR/PLUG

RJ-45 8P for transparent color

Gold Plated:	**1U˚**
Contact Blade:	**Copper/Alloy**
Temperature Range:	**-20° to 75° C**
Dielectric withstanding voltage:	**500V AC**
Insulation Resistance:	**35M Ohm (max.)**
UL Applications:	**250V AC, PC UL94-V-0**

ORDERING INFORMATION

CAT6 Patch Cord	
Part Code	**Description**
NCB-C6UXXXR1-Y-LS	Cat6 UTP 24AWG LSZH Patch Cord. XXX stands for color options and Y denotes length

D-Link (India) Limited
Kalpataru Square, 2nd Floor, Kondivita Lane, Andheri-East, Mumbai-400059
Specifications are subject to change without notice.
D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries.
All other trademarks belong to their respective owners.
©2017 D-Link Corporation. All rights reserved. Release 01 (May 2017)